



AKR 300

CONVENIENT AND EASY-TO-USE
OBJECTIVE REFRACTION



AKR 300

A SMART AND CONVENIENT REFRACTION SOLUTION FOR YOUR PRACTICE

SPECIFICATIONS

EASY AND FAST MEASUREMENTS



- Integrated periphery keratometry measurement for contact lens fitting
- Easy measurement of the corneal, pupil, and hard contact lens diameters
- Customization of measurement protocols

INTUITIVE USAGE



- Instant access and display of last 10 measurements stored in memory
- Assistant measurement function
- Unique Technology: «Live mode» to assist measurement

COMPACT AND ERGONOMIC



- 5.7" TFT LCD color touchscreen with 90° tilt capability
- Motorized chin rest for convenient patient positioning
- Easy access to settings and measurement modes

MEASUREMENT MODES

K/R Mode: Continuous Keratometry and Refractometry

REF Mode: Refractometry

KER Mode: Keratometry

CLBC Mode: Contact Lens Base-Curve Measurement

K(P) Mode: Peripheral Keratometry

REFRACTION MEASUREMENT

Sphere -25.00D to +22.00D (0.12D and 0.25D)

Cylinder -0.00D to ± 10.00 (0.12D / 0.25D)

Axis 0° to 180° (1°)

VD (Vertex Distance) 0.0, 12.0, 13.5, 15.0

PD measurement: 10 - 88 mm (1 mm)

Minimum measurable pupil diameter - 3 mm

KERATOMETRY MEASUREMENT

Corneal curvature radius 5.00 to 10.20 mm (0.01 mm)

Corneal refraction 67.5D to 33.00D (0.05D / 0.12D / 0.25D)

Corneal astigmatism 0D to $\pm 15D$ (0.05D / 0.12D / 0.25D)

Astigmatism axis 0° to 180° (1°)

OTHERS

Corneal diameter 2.00 to 14.00 mm (0.01 mm)

Data memory: 10 measured values for each eye

Screen 5.7", Color TFT LCD (touchscreen)

Dimensions and weight 10 (W) x 20 (D) x 18 (H) in. - 44 lbs

Integrated printer with auto-cutter function

External output terminal: USB (import), RS 232C (export)

Power-supply 100-240 V AC, 50-60 Hz

As improvements are made, these specifications and pictures are not contractually-binding and may be changed without prior notice.



Essilor Instruments USA

8600 W. Catalpa Avenue

Suite 703

Chicago, IL 60656 - USA

Phone: 855.393.4647

Email: info@EssilorInstrumentsUSA.com

www.EssilorInstrumentsUSA.com